



RANGE ROVER

45,000 MILE/72,000 KILOMETER SERVICE CHECKLIST 1993/1994 MODELS

Owner's Name: _____ Date: _____ R.O.#: _____

REQUIRED MAINTENANCE

- Change engine oil: API SE or SF or SE/CC, SF/CC
- Replace engine oil filter
- Check exhaust system for leaks, condition and damage
- Check condition of drive belts - adjust if required - see Workshop Manual for specifications
- Check/top up cooling system *

RECOMMENDED MAINTENANCE

- Check/top up transfer gearbox oil: ATF DEXRON II
- Check/top up automatic transmission fluid: ATF DEXRON II
- Check/top up front axle oil: EP 80W/90 gear oil (GL 4 or 5)
- Check/top up steering swivel housing oil: EP 80W/90 gear oil (GL 4 or 5)
- Check/top up rear axle oil: EP 80W/90 gear oil (GL 4 or 5)
- Check/top up power steering reservoir: ATF DEXRON II
- Lubricate front and rear drive shaft universal joints: Multi-purpose lithium grease
- Lubricate front and rear drive shaft slip joints: Multi-purpose lithium grease
- Check torque of drive shaft coupling bolts: 30-38ft.lbs (41-52 Nm)
- Lubricate parking brake linkage: General purpose grease
- Check operation of parking brake - adjust if required
- Check for oil/fluid leaks from shock absorbers and load levelling unit (if equipped)
- Check Electronic Air Suspension (EAS) air lines, fittings and air springs for routing, leaks and condition (if equipped)
- Check EAS height sensors and electrical harness for damage (if equipped)
- Check brake lines, hoses and unions for condition, routing and leaks
- Check power steering system for leaks; hydraulic hoses and unions for routing and condition
- Check condition of steering box, linkage, ball joints and dust covers
- Check steering box lash - adjust if required
- Check fuel lines for routing and condition, and fuel system for leaks
- Inspect brake pads for wear, calipers for leaks, and discs for condition
- Change brake fluid - bleed system: DOT 4 Brake fluid
- Check foot brake operation
- Clear sunroof drain tubes

Continued on reverse side