



# RANGE ROVER

## 7,500 MILE/12,000 KILOMETER SERVICE CHECKLIST 1993/1994 MODELS

Owner's Name: \_\_\_\_\_ Date: \_\_\_\_\_ R.O.#: \_\_\_\_\_

### REQUIRED MAINTENANCE

- Change engine oil: API SE or SF or SE/CC, SF/CC
- Replace engine oil filter
- Check exhaust system for leaks, condition and damage
- Check condition of drive belts: adjust if required (see Workshop Manual for specifications)
- Check/top up cooling system \*

### RECOMMENDED MAINTENANCE

- Check/top up transfer gearbox oil: ATF DEXRON II
- Check/top up automatic transmission fluid: ATF DEXRON II
- Check/top up front axle oil: EP 80W/90 gear oil (GL 4 or 5)
- Check/top up steering swivel housing oil: EP 80W/90 gear oil (GL 4 or 5)
- Check/top up rear axle oil: EP 80W/90 gear oil (GL 4 or 5)
- Check/top up brake fluid reservoir: DOT 4 Brake fluid
- Check/top up power steering reservoir: ATF DEXRON II
- Lubricate front and rear drive shaft universal joints: Multi-purpose lithium grease
- Lubricate parking brake linkage: General purpose grease
- Check operation of parking brake - adjust if required
- Check brake lines, hoses and unions for condition, routing and leaks
- Check for oil/fluid leaks from shock absorbers and load levelling unit (if equipped)
- Check power steering system for leaks; hydraulic hoses and unions for routing and condition
- Check fuel lines for routing and condition, and fuel system for leaks
- Inspect brake pads for wear, calipers for leaks, and discs for condition
- Check foot brake operation
- Check tires for cuts, lumps, bulges, tread wear; and road wheels for damage
- Check that tires comply with manufacturer's specifications

Continued on reverse side

- [ ] Check/adjust tire pressure - Front: 28PSI (1.9 BAR); Rear 38PSI (2.6 BAR)
- [ ] Check spare tire pressure - inflate to 38PSI (2.6 BAR)
- [ ] Torque road wheel lug nuts: 90-95ft.lbs. (122-129Nm)
- [ ] Clear sunroof drain tubes
- [ ] Check operation of door, hood, tailgate locks and window controls
- [ ] Check condition and operation of seats, seat belt mountings, belts and buckles - including memory feature (County LWB)
- [ ] Check operation of all instruments, gauges, warning indicators, lamps, horn and audio system
- [ ] Clean and grease battery terminals: petroleum jelly
- [ ] Re-code stereo and test drive vehicle - verify Electronic Air Suspension operation (if equipped)

**\* Recommended maintenance in California**

**YOUR NEXT SERVICE IS DUE IN SIX (6) MONTHS OR 7,500 MILES  
(12,000 KM), WHICHEVER IS SOONER**

**PLEASE REFER TO YOUR OWNER'S MANUAL FOR INFORMATION  
REGARDING SERVICE RECOMMENDATIONS AND INTERVALS IF  
YOUR VEHICLE IS USED EXTENSIVELY OFF-ROAD, OR UNDER  
SEVERE OPERATING CONDITIONS**